

REC'D 26 JUL 2004

WIPO

PCT

# THE UNITED STATES OF AMERICA

**TO ALL TO WHOM THESE PRESENTS SHALL COME;**

**UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office**

July 22, 2004

**THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM  
THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK  
OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT  
APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A  
FILING DATE.**

**APPLICATION NUMBER: 60/477,648**

**FILING DATE: June 10, 2003**

**RELATED PCT APPLICATION NUMBER: PCT/US04/18495**

**By Authority of the  
COMMISSIONER OF PATENTS AND TRADEMARKS**



*T. Wallace*  
**T. WALLACE**  
Certifying Officer

**PRIORITY DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH  
RULE 17.1(a) OR (b)

**BEST AVAILABLE COPY**

16138 U.S. PTO  
06/10/03

06-12-03 60477648 0610A1001

Please type a plus sign (+) inside this box → ☐

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.  
PTO/SB/18 (02-01)  
Approved for use through 10/31/2002. OMB 0651-0032  
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

# PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

Express Mail Label No. EIU912815444US

14772 U.S. PTO  
60477648

INVENTOR(S)					
Given Name (first and middle (if any))		Family Name or Surname		Residence (City and either State or Foreign Country)	
Sridhar Joel A.		Kota Hetrick		Ann Arbor, MI Ann Arbor, MI	
<input type="checkbox"/> Additional inventors are being named on the ___ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
Compliant Windshield Wiper Systems					
Direct all correspondence to: CORRESPONDENCE ADDRESS					
<input type="checkbox"/> Customer Number				Place Customer Number Bar Code Label here	
OR Type Customer Number here					
<input checked="" type="checkbox"/> Firm or Individual Name		Benita J. Rohm			
Address		ROHM & MONSANTO, P.L.C.			
Address		660 Woodward Ave., Suite 1525			
City		Detroit		State	MI
Country		USA		ZIP	48226
		Telephone	313965-1976	Fax	313-965-1951
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification		Number of Pages		14	
<input checked="" type="checkbox"/> Drawing(s)		Number of Sheets		8	
<input type="checkbox"/> Application Data Sheet		See 37 CFR 1.76		<input checked="" type="checkbox"/> Other (specify) Cert. of Ex. Mail	
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.				FILING FEE AMOUNT (\$)	
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:				50-0720	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.				80.00	
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are:					

Respectfully submitted,

SIGNATURE

TYPED or PRINTED NAME Benita J. Rohm

TELEPHONE 313-965-1976

Date 6/10/03

REGISTRATION NO.  
(if appropriate)  
Docket Number:

28,664

RM. IMB

## USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE


ATT'Y. DKT.	:	RM.IMB	)
APPLICANT	:	Sridhar Kota and Joel A. Hetrick	)
SERIAL NO.	:		)
FILED	:	June 10, 2003	)
		(By Express Mail)	)
FOR	:	Compliant Windshield Wiper Systems	)

**CERTIFICATE OF MAILING  
BY  
EXPRESS MAIL**

Express Mail Label Number EU912815444US

Date of Deposit June 10, 2003

I hereby certify that a Provisional Application Under 37 C.F.R. § 1.53(b)(2) in the names of inventor(s) Sridhar Kota and Joel A. Hetrick, a Provisional Application Cover Sheet, Specification (14 pages), eight (8) sheets of drawings, are being deposited with the United States Postal Service under 37 C.F.R. § 1.10 as Express Mail Post Office to Addressee on the date indicated hereinabove and addressed to Box Provisional Patent Application, Commissioner for Patents, Washington, DC 20231.

  
Benita J. Rohm, Reg. No. 28,664  
**ROHM & MONSANTO, PLC**  
660 Woodward Avenue, Suite 1525  
Detroit, MI 48226  
(313) 965-1976

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

**PROVISIONAL APPLICATION FOR UNITED STATES LETTERS PATENT**

Express Mail Label No.	:	EU912815444US
Date Deposited	:	June 10, 2003
Attorney Docket No.	:	RM-IMB
No. of Dwg. Figs./Sheets	:	9/8
No. of Claims -		
Independent	:	n/a
Total	:	n/a

**Compliant Windshield Wiper Systems**

by

Sridhar Kota

and

Joel A. Hetrick

**ROHM & MONSANTO, P.L.C.**

*Attorneys at Law*

660 WOODWARD AVENUE, SUITE 1525

DETROIT, MICHIGAN 48226

TELEPHONE (313) 965-1976

TELECOPIER (313) 965-1951

[0001]

**Compliant Windshield Wiper Systems****[0002] Background of the Invention****[0003] FIELD OF THE INVENTION**

[0004] This invention relates generally to compliant structures, and more particularly to a windshield wiper arrangement that is provided with a single-piece force distribution arrangement.

**[0005] DESCRIPTION OF THE RELATED ART**

[0006] Traditional automotive windshield wipers that incorporate rigid-link whiffletree structures provide substantially equal force distribution from the center input arm to the plural output connectors. The output connectors provide discrete, but equal, force transfer to the rubber wiper (which is typically reinforced with a steel or plastic runner that aids force distribution). The traditional rigid-link approach requires many separate parts to be designed, manufactured, and assembled.

[0007] It is, therefore, an object of this invention to provide a windshield wiper arrangement that can be constructed of a minimal number of separate parts.

[0008] It is another object of this invention to provide a windshield wiper arrangement that applies a predetermined distribution of force in the direction of the windshield.

[0009] It is also an object of this invention to provide a windshield wiper arrangement that applies a force in the direction of the windshield in accordance with a predetermined distribution over a range of windshield contours.

**[0010] Summary of the Invention**

[0011] The foregoing and other objects are achieved by this invention which provides, in accordance with a first apparatus aspect thereof, a windshield wiper arrangement for a windshield of a vehicle. The windshield wiper arrangement is coupled to a windshield wiper arm that is coupled at a first end thereof to the vehicle and at a second end thereof to the windshield wiper arrangement for applying

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

a force thereto with respect to the vehicle in a direction that urges the windshield wiper arrangement toward the windshield. The windshield wiper arm additionally moves the windshield wiper arrangement across the windshield. A windshield wiper blade is coupled to the windshield wiper arrangement for communicating with the windshield of the vehicle, the windshield wiper arrangement is further provided with a windshield wiper blade support that is formed of a resilient material, and has a primary beam having first and second ends, the primary beam being arranged to be coupled with the windshield wiper arm in a coupling region intermediate of the first and second ends to define first and second portions of the primary beam between the coupling region and the first end, and between the coupling region and the second end, respectively. A first compliant beam portion is formed integrally with the primary beam, the first compliant beam portion being formed of three compliant sections arranged as an end-point triangle having three compliant section junctures. The first compliant beam portion is coupled at one of the three compliant section junctures to the first end of the primary beam and the remaining two compliant section junctures are arranged to couple with the windshield wiper blade. A second compliant beam portion also is integrally formed with the primary beam, the second compliant beam portion being formed of two compliant sections arranged as a triangle with a portion of the first portion of the primary beam forming a leg of the triangle. A compliant section juncture distal from the first portion of the primary beam is arranged to couple with the windshield wiper blade. Also, there is provided a third compliant beam portion that is integrally formed with the primary beam. The third compliant beam portion is formed of two compliant sections arranged as a triangle with a portion of the second portion of the primary beam forming a leg of the triangle. A compliant section juncture distal from the second portion of the primary beam is arranged to couple with the windshield wiper blade.

XX

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

[0012] In a specific illustrative embodiment of the first apparatus aspect, there is provided a fourth compliant beam portion integrally formed with the primary beam. The fourth compliant beam portion is formed of three compliant sections arranged as an end-point triangle having three compliant section junctures. The first compliant beam portion is coupled at one of the three compliant section junctures to the second end of the primary beam and the remaining two compliant section junctures are arranged to couple with the windshield wiper blade.

[0013] In a further embodiment, the two compliant sections are arranged as a triangle of the second compliant beam portion and are angled such that the compliant section juncture distal from the first portion of the primary beam is disposed in a spatial region intermediate of the further portion of the first portion of the primary beam that forms a leg of the triangle and the coupling region intermediate of the first and second ends of the primary beam.

[0014] In a still further embodiment of the invention, the two compliant sections that are arranged as a triangle of the third compliant beam portion are angled such that the compliant section juncture distal from the second portion of the primary beam is disposed in a spatial region intermediate of the further portion of the second portion of the primary beam that forms a leg of the triangle and the coupling region intermediate of the first and second ends of the primary beam.

[0015] A fourth compliant beam portion is, in certain embodiments, integrally formed with the primary beam. The fourth compliant beam portion is formed of two compliant sections arranged as a triangle with a further portion of the first portion of the primary beam forming a leg of the triangle. A compliant section juncture distal from the first portion of the primary beam being arranged to couple with the windshield wiper blade. In some embodiments, the two compliant sections arranged as a triangle of the fourth compliant beam portion are angled such that the compliant section juncture

distal from the first portion of the primary beam is disposed in a spatial region intermediate of the further portion of the first portion of the primary beam that forms a leg of the triangle and the coupling region intermediate of the first and second ends of the primary beam.

[0016] There is additionally provided in a specific embodiment a fifth compliant beam portion integrally formed with the primary beam. The fifth compliant beam portion is formed of two compliant sections arranged as a triangle with a further portion of the second portion of the primary beam forming a leg of the triangle, a compliant section juncture distal from the second portion of the primary beam being arranged to couple with the windshield wiper blade.

[0017] **Brief Description of the Drawing**

[0018] Comprehension of the invention is facilitated by reading the following detailed description, in conjunction with the annexed drawing, in which:

[0019] Fig. 1 is a simplified schematic representation of a compliant structure that shows the distribution and magnitudes of certain output forces in proportion to an input force;

[0020] Fig. 2 is a simplified schematic representation of a further compliant structure that shows the distribution and magnitudes of certain output forces in proportion to an input force;

[0021] Fig. 3 is a simplified schematic representation of a compliant structure similar to that of Fig. 1 showing an asymmetrical distribution output forces in magnitudes proportioned to an input force;

[0022] Fig. 4 is a simplified schematic representation of a composite compliant structure showing a distribution output forces in magnitudes proportioned to an input force derived from a windshield wiper arm;



[0023] Fig. 5 is a simplified schematic representation of a further composite compliant structure showing a distribution output forces in magnitudes proportioned to an input force derived from a windshield wiper arm;

[0024] Fig. 6 is a simplified schematic representation of a composite compliant structure that has been optimized to achieve a substantially equalized distribution of output forces in magnitudes proportioned to an input force derived from a windshield wiper arm over a range of windshield curvatures;

[0025] Fig. 8 is a simplified schematic representation of the result of a nonlinear finite element analysis showing the initial shape of the windshield wiper blade (top image) and the stress distribution in the windshield wiper blade as it conforms to a curved boundary (windshield) (lower image) wherein near equal force distribution is obtained for flat to highly curved boundaries; and

[0026] Fig. 9 is a CAD representation of a specific illustrative embodiment of the invention.

[0027] **Detailed Description**

[0028] Using structural optimization techniques, there is presented herein a single-piece (monolithic) windshield wiper system wherein members (beams) within the structure bend to allow the structure to conform to various windshield curvatures. In this arrangement, the input force is efficiently transmitted primarily along the axis of each member such that equal, or near equal, force distribution is achieved at the output connectors. The present device therefore mimics the functionality of a rigid-link whiffletree using only one part that can easily and inexpensively be injection molded. Accordingly, fabrication of the intricate mechanism is achieved in a single step without requiring assembly.

US 2017/0144433 A1

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

[0029] Materials that are useful in the fabrication of the inventive windshield wiper arrangement primarily include high-strength, temperature-stable, and ultraviolet resistant polymers, such as polystyrene and polycarbonate. Other materials such as high density polyethylene (HDPE), acrylonitrile butadiene styrene (ABS), Nylon, metal, composites, ceramics, *etc.* can also be adapted for use in the inventive structure. Still further materials include filled materials, such as fiber reinforced materials that are resistant to degradation and plastic creep resulting from environmental conditions. These include, for example, glass filled polycarbonate, glass filled ABS (Acrylonitrile Butadiene Styrene), and glass filled nylon. Yet another polymer that is useful in this application is polyphenylsulfone.

[0030] The following describes the basic theory for designing the monolithic building block structures of the present invention, there being further provided hereinbelow images of optimization models, detailed finite element models, and CAD models.

[0031] Fig. 1 is a simplified schematic representation of a compliant structure that shows the distribution and magnitudes of certain output forces in proportion to an input force. As shown in this figure, the input force,  $F_{in}$  is divided equally at the outputs (lower downward arrows) so as each to have a magnitude of  $\frac{1}{2}F_{in}$ .

[0032] Fig. 2 is a simplified schematic representation of a further compliant structure that shows the distribution and magnitudes of certain output forces in proportion to an input force. As shown in this figure, the input force is distributed in response to the dimensions of the various members. More specifically, the input force,  $F_{in}$  is divided equally at the force outputs, as follows:

[0033] 
$$F_{out1} = F_{out2} = \frac{1}{2}F_{in}$$

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

[0034] Fig. 3 is a simplified schematic representation of a compliant structure similar to that of Fig. 1 showing an asymmetrical distribution output forces in magnitudes proportioned to an input force. In this figure, it is seen that unequal output forces, that are predetermined fractions of the input force,  $F_{in}$ , are achieved in response to inequality of the segments, as follows:

[0035] 
$$F_{out1} = \frac{l_2}{l_1 + l_2} F_{in}$$

[0036] 
$$F_{out2} = \frac{l_1}{l_1 + l_2} F_{in}$$

[0037] It is to be understood that the force relationships set forth herein are but approximations. The forces in certain embodiments of the invention are functions of (1) the thickness and width of the beams; (2) the undeformed geometry (slopes) of the beams; (3) the magnitude of the input force; and (4) the slope of the surface (angle) to which the deformed structure must conform. Thus, the relationships discussed herein are useful to determine an approximate topology and geometry of the wiper structure, which can further be refined during structural optimization.

[0038] Fig. 4 is a simplified schematic representation of a composite compliant structure showing a distribution of output forces in magnitudes proportioned to an input force derived from a

SECRET

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

windshield wiper arm. This figure shows each of four outputs producing an output force magnitude of  $\frac{1}{4}F_{in}$ .

[0039] In this figure, it is seen that first and second sets of two compliant segments each are coupled to form respective ones of first and second triangular structures wherein one leg of each such triangular structure is a respective portion of the principal beam itself. These first and second triangular structures therefore are distinguishable from the distal-most triangular structure that is seen in the figure to be formed of three compliant segments that are coupled at a juncture thereof to the end point of the principal beam. Thus, the principal beam does not constitute a leg of the distal-most triangular structure.

[0040] Fig. 5 is a simplified schematic representation of a further composite compliant structure showing a distribution output forces in respective magnitudes that are proportioned to an input force that is derived from a windshield wiper arm. As shown in this figure, the windshield wiper arm is coupled to a juncture of a first tier triangular structure. The remaining juncture points of the first tier triangular structure are coupled to respective second tier triangular structures that provide the force outputs at their remaining juncture points. In this specific illustrative embodiment of the invention, each of the four outputs produces an output force magnitude of  $\frac{1}{4}F_{in}$ .

[0041] Figs. 6 and 7 are simplified schematic representations of a composite compliant structure that is similar to that of Fig. 4, discussed hereinabove, and that has been optimized to achieve a substantially equalized distribution of output forces in magnitudes proportioned to an input force derived from a windshield wiper arm over a range of windshield curvatures.

[0042] Fig. 8 is a simplified schematic representation of the result of a nonlinear finite element analysis showing the initial shape of a windshield wiper blade (top image) and the stress distribution

2025 RELEASE UNDER E.O. 14176

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

in the windshield wiper as it conforms to a curved boundary (windshield) (lower image) wherein near equal force distribution is obtained for flat to highly curved boundaries.

[0043] Fig. 9 is a CAD representation of a specific illustrative embodiment of the invention. It is seen from the foregoing that the present compliant structure relies principally on the compliant nature of the beams and legs of the triangular sections themselves to achieve the desired force distribution, rather than a compliance characteristic of the joints and junctures of the structure. Thus, in the present situation, there is provided a direct coupling between the principal beam and the point of predetermined force output, *e.g.*, the wiper blade, without requiring a resilient coupling element extending along the wiper blade.

[0044] The embodiments of Figs. 8 and 9 are shown to be symmetrical about a point on the principal beam where the input force is introduced. It is to be understood that the present invention is not limited to symmetrical structural configurations. Thus, a specific illustrative embodiment of the invention may be provided with different compliant structures on either side of the location on the principal beam where the input force is delivered by the wiper arm. Moreover, the present invention is not limited to delivery of the input force at the center of the principal beam. By way of example, an embodiment of the invention may employ the structure depicted schematically in Fig. 1 on one portion of the windshield wiper arrangement, and the structure depicted schematically in Fig. 2 on the other portion.

[0045] Although the invention has been described in terms of specific embodiments and applications, persons skilled in the art may, in light of this teaching, generate additional

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

embodiments without exceeding the scope or departing from the spirit of the invention described herein. Accordingly, it is to be understood that the drawing and description in this disclosure are proffered to facilitate comprehension of the invention, and should not be construed to limit the scope thereof.

\*\*\*\*\*

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

[0046] The following subject matter is in claim-like form, but is not intended to specify every aspect of the invention disclosed in this provisional application to which the inventors herein may be entitled, or otherwise define or limit the invention. This material is provided as additional disclosure.

[0047] 1. A windshield wiper arrangement for a windshield of a vehicle, the windshield wiper arrangement being coupled to a windshield wiper arm that is coupled at a first end thereof to the vehicle and at a second end thereof to the windshield wiper arrangement for applying a force thereto with respect to the vehicle in a direction that urges the windshield wiper arrangement toward the windshield and which moves the windshield wiper arrangement across the windshield, the windshield wiper arrangement having windshield wiper blade coupled thereto for communicating with the windshield of the vehicle, the windshield wiper arrangement further comprising, a windshield wiper blade support formed of a resilient material, the windshield wiper blade support having:

[0048] a primary beam having first and second ends, said primary beam being arranged to be coupled with the windshield wiper arm in a coupling region intermediate of the first and second ends to define first and second portions of said primary beam between the coupling region and the first end, and between the coupling region and the second end, respectively;

[0049] a first compliant beam portion integrally formed with said primary beam, said first compliant beam portion being formed of three compliant sections arranged as an end-point triangle having three compliant section junctures, said first compliant beam portion being coupled at one of the three compliant section junctures to the first end of said primary beam and the remaining two compliant section junctures being arranged to couple with the windshield wiper blade;

507755 051003

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

[0050] a second compliant beam portion integrally formed with said primary beam, said second compliant beam portion being formed of two compliant sections arranged as a triangle with a portion of the first portion of said primary beam forming a leg of the triangle, a compliant section juncture distal from the first portion of said primary beam being arranged to couple with the windshield wiper blade;

[0051] a third compliant beam portion integrally formed with said primary beam, said third compliant beam portion being formed of two compliant sections arranged as a triangle with a portion of the second portion of said primary beam forming a leg of the triangle, a compliant section juncture distal from the second portion of said primary beam being arranged to couple with the windshield wiper blade.

[0052] 2. The windshield wiper arrangement of claim 1, wherein there is further provided a fourth compliant beam portion integrally formed with said primary beam, said fourth compliant beam portion being formed of three compliant sections arranged as an end-point triangle having three compliant section junctures, said first compliant beam portion being coupled at one of the three compliant section junctures to the second end of said primary beam and the remaining two compliant section junctures being arranged to couple with the windshield wiper blade.

[0053] 3. The windshield wiper arrangement of claim 1, wherein the two compliant sections arranged as a triangle of said second compliant beam portion are angled such that the compliant section juncture distal from the first portion of said primary beam is disposed in a spatial region intermediate of the further portion of the first portion of said primary beam that forms a leg of the triangle and the coupling region intermediate of the first and second ends of the primary beam.



PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

- [0054] 4. The windshield wiper arrangement of claim 1, wherein the two compliant sections arranged as a triangle of said third compliant beam portion are angled such that the compliant section juncture distal from the second portion of said primary beam is disposed in a spatial region intermediate of the further portion of the second portion of said primary beam that forms a leg of the triangle and the coupling region intermediate of the first and second ends of the primary beam.
- [0055] 5. The windshield wiper arrangement of claim 1, wherein there is further provided a fourth compliant beam portion integrally formed with said primary beam, said fourth compliant beam portion being formed of two compliant sections arranged as a triangle with a further portion of the first portion of said primary beam forming a leg of the triangle; a compliant section juncture distal from the first portion of said primary beam being arranged to couple with the windshield wiper blade.
- [0056] 6. The windshield wiper arrangement of claim 5, wherein the two compliant sections arranged as a triangle of said fourth compliant beam portion are angled such that the compliant section juncture distal from the first portion of said primary beam is disposed in a spatial region intermediate of the further portion of the first portion of said primary beam that forms a leg of the triangle and the coupling region intermediate of the first and second ends of the primary beam.
- [0057] 7. The windshield wiper arrangement of claim 1, wherein there is further provided a fifth compliant beam portion integrally formed with said primary beam, said fifth compliant beam portion being formed of two compliant sections arranged as a triangle with a further portion of the second portion of said primary beam forming a leg of the triangle, a compliant section juncture distal from the second portion of said primary beam being arranged to couple with the windshield wiper blade.

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

[0058]


**ABSTRACT OF THE DISCLOSURE**

[0059]


A windshield wiper arrangement is coupled to a windshield wiper arm that is coupled at a distal end thereof to the vehicle for applying a force to the windshield wiper arrangement with respect to the vehicle in a direction that urges the windshield wiper arrangement toward the windshield and which moves the windshield wiper arrangement across the windshield. The windshield wiper arrangement has a windshield wiper blade coupled thereto for communicating with the windshield of the vehicle. A windshield wiper blade support formed of a resilient material has a primary beam having first and second ends, the primary beam is arranged to be coupled with the windshield wiper arm in a coupling region intermediate of the first and second ends to define respective ones of first and second portions of the primary beam between the coupling region and the first end, and between the coupling region and the second end, respectively. A first compliant beam portion is integrally formed with the primary beam and formed of three compliant sections arranged as an end-point triangle having three compliant section junctures, the first compliant beam portion is coupled at one of the three compliant section junctures to the first end of the primary beam and the remaining two compliant section junctures is arranged to couple with the windshield wiper blade. A second compliant beam structure is formed of two compliant sections arranged as a triangle with a portion of the first portion of the primary beam forming a leg of the triangle, a compliant section juncture distal from the first portion of the primary beam is arranged to couple with the windshield wiper blade. A third compliant beam structure is formed of two compliant sections arranged as a triangle with a portion of the second portion of the primary beam forming a leg of the triangle, a compliant section juncture distal from the second portion of the primary beam is arranged to couple with the windshield wiper blade.

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

**FIG. 1**




**FIG. 2**



PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

**FIG. 3**




$$F_{out\ 1} = \frac{l_2}{l_1 + l_2} F_{in}$$

$$F_{out\ 2} = \frac{l_1}{l_1 + l_2} F_{in}$$

*Approximate Force Relationship for Whiffletree Building Block*

PROVISIONAL UNITED STATES PATENT APPLICATION  
Sridhar Kota and Joel A. Hetrick


FIG. 4



4 Output (3 whiffletree) Building Block Layout #1

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*


**FIG. 5**



*4 Output (3 whiffletree) Building Block Layout #2*

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*


**FIG. 6**



Optimized wiper design  
 (Equality of output forces were optimized over a range of surface curvatures)

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

**FIG. 7**




Deformed Geometry for Wiper Design  
(Curved Boundary Condition)



PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*


**FIG. 8**



Nonlinear finite element analysis showing the initial shape of the wiper blade (top image). The lower image shows the stress distribution in the wiper as it conforms to a curved boundary (windshield). Near equal force distribution is obtained for flat to highly curved boundaries.

PROVISIONAL UNITED STATES PATENT APPLICATION  
*Sridhar Kota and Joel A. Hetrick*

**FIG. 9**



Detailed Cad Model

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ ~~BLACK BORDERS~~
- ☒ ~~IMAGE CUT OFF AT TOP, BOTTOM OR SIDES~~
- ☒ ~~FADED TEXT OR DRAWING~~
- ☒ ~~BLURRED OR ILLEGIBLE TEXT OR DRAWING~~
- ☒ ~~SKEWED/SLANTED IMAGES~~
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ ~~LINES OR MARKS ON ORIGINAL DOCUMENT~~
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**